Using the Column values of the PTOFBMPPN—
after conversion to PN — generates the very same
"BIM+" [illegible] parameters+" matrix on the BIM.

[illegible] added to bring out the

Downwards Diagonals go to Background Diagonals (P,Y,G)

Columns go Perpendicular to PD

Upward Diagonals go Parallel to PD

10 Parameters ALL MPS follow:

- z=Mp=2^p-1=x+y
  z_n=z_next z value
- z^2=Mp^2=Mersenne Prime Square
  z^2_p=previous
  z^2_n=next
  PN=xz OC=yz
- PN_p=PN_previous
- 4PN=Perfect Number x 4
- CR=xy=Complement Rectangle
  CR_n=CR_next
  y=x-1=z_prev=z-x
  z^2+4x=4PN

4PN + 2x = PNnext
(4•28)+2(4)=120

Δ 4PN - 4x = 4PNprevious
EX: 24 - 16 = 8
32 = 24
4= 56
-120

x=z-y=PN/z=2^{p-1} • 4x--8x--16x... expansion*

GREEN Line
GREEN Line
PURPLE Line
YELLOW Line
YELLOW Line
RED Line

10 Parameters on the UPPER diagonal side of the Diamond become the expanded parameters on the LOWER diagonal side, that itself is the UPPER side of the "next" Diamond. ALL parameters are connected and related this way, giving [illegible]e to the straight-line [illegible]rectors.

[illegible]g paths PARALLEL to the PD, from bottom to the top of the DMPS.

[illegible]e DMPS to another.

[illegible]" Axis by the "z" Axis to give the PN (containers) as the [illegible] That gives the sequence number spacing as:

[illegible]n Diagonal path on the BIM, it does so in a

[illegible]PS of STEPS both along the Parallel

[illegible]indicate the Column "z" [illegible]nage as located within

[illegible]MES.

Copyright©2022-23, Reginald Br[illegible]s, Brooks Design. All rights reserved.